

US005128785A

United States Patent [19]

Yoshimoto et al.

[11] Patent Number:

5,128,785

[45] Date of Patent:

Jul. 7, 1992

[54] LIQUID CRYSTAL DISPLAY DEVICE SUBSTANTIALLY FREE FROM CROSS-TALK HAVING VARISTOR LAYERS COUPLED TO SIGNAL LINES AND PICTURE ELECTRODES

[75] Inventors: Hataaki Yoshimoto, Chiba; Katsuhiro

Ito; Hiroyuki Mori, both of Ichihara,

all of Japan

[73] Assignee: Ube Industries, Ltd., Yamaguchi,

Japan

[21] Appl. No.: 563,184

[22] Filed: Aug. 6, 1990

[30] Foreign Application Priority Data Aug. 8, 1989 [JP] Japan 1-203751

Sep. 27, 1989	[JP]	Japan	 1-249000
Sep. 27, 1989		Japan	 1-249001
Sep. 27, 1989		Japan	 1-249002
Sep. 28, 1989		Japan	 1-250721
Sep. 28, 1989		Japan	 1-250722
Oct. 3, 1989		Japan	 1-256955
Oct. 12, 1989			
OCL. 12, 1707	[2.7.]	Jupun	

[51]	Int. Cl.5	G02F 1/133
[52]	U.S. Cl	
[]	•	

[56] References Cited

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

OTHER PUBLICATIONS

D. E. Castleberry "Varistor Controlled Multiplexed Liquid Crystal Display", Conference Record of the 1978 Biennial Display Research Conference, N.Y., U.S.A.-Oct. 1978-pp. 42-43.

D. E. Castleberry "Varistor-Controlled Liquid-Crystal Displays" IEEE Transactions on Electron Devices, vol. ED 26. No. 8, Aug. 1979-pp. 1123-1128.

Castleberry-"Control Layers for Liquid Crystal Matrix Displays" IEEE 1980 Biennial Display Research Conference-1980-pp. 89-92.

Primary Examiner—Stanley D. Miller Assistant Examiner—Tai V. Duong Attorney, Agent, or Firm—Finnegan, Henderson, Farabow, Garrett & Dunner

57] ABSTRACT

A liquid crystal display device capable of displaying clear images without cross-talk, comprises (a) a first transparent base, (b) a plurality of picture element electrodes on the first base (a), (c) a plurality of signal lines on the first base (a), (d) a plurality of varistor layers connecting the picture element electrodes (b) to the signal lines (c) therethrough, (e) a second transparent base in parallel to the first base (a), (f) a plurality of electrodes on the second base (e), and (g) a liquid crystal material layer arranged between the picture element electrodes (b) and the electrode (f), and is characterized in that portions of the varistor layer connecting the signal lines (c) and the adjacent picture element electrode (b) have a threshold value voltage (V_{th}) smaller than a minimum voltage (V_{min}) at which an electric current is allowed to flow from the signal lines (c) to the electrodes (f) through at least portions of the varistor layers extending from the signal lines (c) toward the electrodes (f).

15 Claims, 3 Drawing Sheets

